

The topical subject ...

One-off oil for furniture, doors, floors ...

AURO One-off oil No. 109

AURO One-off oil, natural No. 109-90

- Apply
- Remove surplus oil
- Done!

Protection and beauty for your wood

Single Application Oil is suitable for all customary kinds of wood and indoor applications. Normally, just a single application will be sufficient to give raw wood an easy-care, attractive finish. Application on previously oiled surfaces increases the protective effect and highlights the natural wood colour.

Fluctuations in moisture are controlled and the resistance properties are improved.

The delicate white pigmentation of One-off oil, natural - enhances the colour of the wood and is ideal for wood of a lighter shade (maple, ash and birch).

Application couldn't be easier!

AURO One-off oil is applied with a brush, roller or a non-fluffing cloth on the surface that is to be treated. Areas where the oil is rapidly soaked up should be re-saturated wet-on-wet up to three times, depending on the given requirements. After a venting time of approx. 20 minutes, all surplus oil should be rubbed into the wood, and finally removed, with a polishing pad or cloth.

In the event of considerable surplus oil then this can be removed with oil-resistant wipers or spatulas made of metal or plastic and collected for renewed use.



AURO One-off oil No. 109



AURO One-off oil, natural No. 109-90

Rubbing-in or removal of all surplus oil will result in an evenly satin mat surface. Limited load is possible after 24 hours. Clean dry (not wet) in the first weeks after application.

Please turn over!

Care and cleaning

Wood surfaces treated with AURO One-off oil should be re-oiled when necessary, i.e. depending on the degree of wear and tear. For this purpose clean the surfaces with a mild cleaning agent, e.g. AURO Paint and stain cleaner No. 435. This is then followed by after-care with One-off oil applied with a non-fluffing cloth or a polishing pad for floors.

To offset wear symptoms as soon as possible we recommend care with AURO Care oil No. 106. If the surface is waxed, then AURO Care wax No. 107 should be applied so that the surface becomes once again resistant to dirt and water (see green box).

Tool use and tool cleaning

Products that contain drying oil can ignite spontaneously, particularly if cloths are crumpled. Consequently, all used cloths should be individually spread out and smoothed and allowed to dry. The used cloths must definitely not be crumpled! Dried cloths can be disposed of with the domestic waste or, if required, stored for reuse.

Clean brushes with AURO Thinner No. 191 and then wash them with AURO Plant soap No. 411 and rinse in water. Rub AURO Plant soap No. 411 into brushes and surface coaters and store the tools in this manner. Before they are used again wash the tools in water.

Product storage and safety

As is the case with all paints and coating materials, the original container of One-off oil must be kept tightly closed and stored in a cool, but frost-free place well out of reach of children. When stored in this manner the guaranteed storage stability is 24 months. Normally the products can be used beyond this period, but always conduct a test application beforehand. When applying oils - as is customary with paints and varnishes - ensure that the appropriate protection measures are always observed, especially fresh-air ventilation and skin protection.

Care of oiled and waxed surfaces

Treatment with natural oils and waxes gives wood surfaces brilliance and highlights the specific grain and structure of the wood. Moreover, the surfaces are given dirt and water repelling properties which is combined with an anti-static effect. Contrary to varnished surfaces, bases treated in this manner retain their respiratory properties, thereby contributing to the regulation of the room climate.

Depending on the stresses to which the oiled/waxed surfaces are exposed, the immediate contact area is subject to mechanical wear. Sooner or later this becomes particularly apparent on floors, work surfaces and tables. Apart from the deterioration of appearance, surface wear becomes increasingly susceptible to liquids and dirt deposits. AURO Care oil No. 106 and Care wax No. 107 counteract these wear symptoms.

Your AURO dealer will be happy to advise you in this respect.

Please also refer to our information on Care oil and Care wax!

