

Volvox Casein Filler

1. Use

Volvox Filler is suitable for sound, absorbent surfaces to level cracks and unevenness and to fill holes and gaps. It is used prior to painting with **earthBorn** Wall & Ceiling Paints and Clay Plasters.

2. Product Codes

500g 1.1811
2kg 1.1812

3. Coverage

1.5 kg per m² per mm of thickness of coating

4. Colour

White

5. Drying Time

Approx. 4 hours, ready for sanding down after 8-12 hours.

6. Instructions for Use

The surfaces should be clean and grease-free. Water-soluble old coats of distempers or lime-paints must be removed. Any loose material should be brushed off. 1 kg of Filler should be mixed with 150 ml water until a lump-free paste is obtained. If necessary add some water during application.

If colouring the filler with earthBorn pigments, the dry powder must be carefully mixed with the pigment first then the required water added. Apply the ready-mixed filler to create an even surface. If necessary level-out deep holes and cracks a second time.

Note: The whitening and covering power will only be visible when the product is fully dry.

7. Tools

Spatula or knife

8. Storage

Cool, dry, frost-free

9. Ingredients

Powdered marble, lime hydrate, white cement, cellulose, clay, casein

10. Safety

Alkaline. Irritating to eyes and skin. Keep out of the reach of children.

11. Disposal

Allow unused paint to dry and dispose of safely according to local authority disposal guidelines.

The user is recommended to test the product on the intended surface to ensure its suitability