

Volvox Wallpaper Paste

1. Use

Volvox Wallpaper paste is suitable for hanging wallpapers on absorbent surfaces. Note it can also be used in paste-like form as a non-hazardous finger paint.

The user is recommended to test the product on the intended surface to ensure its suitability

2. Product Codes

100g 1-6101

500g 1-6102

Usage: 100g mixed in 5ltrs of warm water covers 28m² for medium weight wallpaper.

3. Instructions for Use

Disperse Volvox Wallpaper Paste into water while stirring constantly until a lump free paste is obtained. For best results use warm water. Leave to stand for approx 30 minutes and stir thoroughly once more. Apply to wallpaper with a brush or a wallpaper paste machine, ensuring the edges of the wallpaper are fully covered. Attach the wallpaper to the wall pressing evenly and firmly to avoid the formation of air pockets. It is recommended to roller the seams to ensure good adhesion.

4. Tools

Brush

5. Storage

Keep containers tightly sealed and store in a cool but frost-free and dry place.

6. Ingredients

Pure methyl cellulose of various fibre lengths. Guaranteed free from fungicides, preservatives and synthetic resins.

7. Safety

Even though non-hazardous, keep out of the reach of children.

8. Disposal

Allow unused wallpaper paste to dry and dispose of safely and according to local authority disposal guidelines.