

Special product



Wallpaper paste

No. 389



- > High adhesive power
- > Ideal for handicrafts
- > Easy application

200 g

Wallpaper paste No. 389

Use: For gluing lightweight, medium-weight to heavy paper-backed wallpaper. Also suitable for handicrafts. Not suitable for vinyl foam wallpaper.

Preparation: Substrates must be solid, dry and clean. Fill and surface cracks and holes with AURO Natural wall filler no. 329. Stabilise crumbling plaster with AURO Plaster primer no. 301, if necessary, pretreat absorptive substrates with a layer of wallpaper paste. Sand down sintered skin on new plaster, brush down water marks.

Application: Add powder to cold water evenly and stir until lump-free. Allow to swell for 1 h and stir well again. Pretreat walls and ceilings with a layer of wallpaper paste. Apply wallpaper paste to wallpaper with a wide paint brush or mechanically, allow to soak and hang wallpaper; work particularly careful in seam edge areas. Observe soaking time specified by wallpaper manufacturer. **Overcoatable** after 24-48 h. Use up mixed wallpaper paste within 3 days. Observe DIN 18366 and BFS Information Sheet No. 16.

Cleaning: Dab wallpaper paste stains with a damp cloth, do not rub. Clean tools with water. Composition: cellulose ether.

Packaging material: soda kraft paper with PE inner lining.

Processing:	Mixing ratio per 200g	water	200 g suffice per ca.	Coverage for approx.
Pre-pasting	1:80	16 l	120 - 160 m²	1,5 g/m²
light wallpaper	1:50	10 l	80 - 100 m ²	2,2 g/m ²
medium/heavy wallpaper	1:45	91	60 - 80 m²	2,9 g/m²
heavy wallpaper raw fiber paper	1:40	81	40 - 60 m²	4,0 g/m ²

Storage stability approx. 24 months. **Disposal:** Compost dried product residues or dispose of along with domestic waste. Liquid residues: EWC code 200128.

Made in Germany AURO Pflanzenchemie AG Alte Frankfurter Str. 211 D-38122 Braunschweig Tel. +49 531-281 41 0 www.auro.de



