# DOUGLAS FIR PROTECTION treatex®

Treatex Douglas Fir Protection is a solvent free exterior wood finish which offers long lasting weather protection. This product is manufactured on a base of natural sustainable raw materials: linseed oil, sunflower oil and soybean oil. Treatex Douglas Fir Protection is designed for use on timbers like douglas fir. It is not suitable for timbers which contain tannins, such as oak. Treatex Douglas Fir Protection is the ideal finish for decking, garden furniture, fences and other exterior joinery.

- Easy to apply
- UV resistant
- Highly water resistant
- Solvent free
- Safe for use on children's toys
- Suitable for indoor and outdoor use
- Will not flake or peel



## Preparation

Treatex Douglas Fir Protection will only work on unfinished timber. Previous finishes must be fully removed prior to application. Ensure the timber is dry and free from possible contaminates e.g. algae, grease, dirt, dust etc. Timbers susceptible to decay, mould and fungi should be treated first with a suitable preservative. We advise that when using Treatex Douglas Fir Protection, sufficient product is purchased to complete the whole project and when more than one tin is required it is advisable to mix them together before use. Timber must have a moisture content below 18%. Temperature must be greater than 8°C during application and drying. We strongly recommend a trial application prior to starting the project.

# Application of Treatex Douglas Fir Protection

Do not apply in damp, humid conditions. Stir container thoroughly, before and during use. Use a brush to evenly apply Treatex Douglas Fir Protection in the same direction as the wood grain, allowing approximately 125ml per m<sup>2</sup>. Pay particular attention to end grain, on end grain apply wet on wet until product is no longer absorbed by the timber. After approximately 3–6 hours the first coat can be overcoated. The second coat must be applied within 24 hours. Apply with a brush a second coat of Treatex Douglas Fir Protection, again allowing roughly 125ml per m<sup>2</sup>. After the second coat it will take up to 24 hours for the product to fully dry.

### Tips

This product can look milky when first applied however it dries to a transparent brown. Treatex brushes are available. Wet brushes can be cleaned with warm soapy water. Store containers in a cool and frost free environment. Unopened containers will last for three years. Once containers are opened, transfer contents to a smaller airtight container.

#### Coverage

2.5 litres covers approximately 20m<sup>2</sup> one coat depending on timber and method of application.

#### Contact

Treatex Ltd, Unit I, Howland Road Business Park, Howland Road, Thame, Oxfordshire, OX9 3GQ. tel: 01844 260416 fax: 01844 358160 email: info@treatex.co.uk www.treatex.co.uk