



Technical data

Material		
Backing	Double-layer special membrane made of PP fleece and TEEE functional film	
Adhesive	Special acrylate adhesive	
Property	Regulation	Value
Colour		Dark grey
sd value	EN ISO 12572	0.05 m
g value	EN ISO 12572	0.25 MN·s/g
Vapour permeance	ASTM E 96	38 perms
Outdoor exposure		3 months
Resistance to driving rain	ift, MO-01/1:2007-01, Abs. 5	Up to 600 Pa, around window
Water column	EN ISO 811	> 2 500 mm ; > 8' 2"
Bond durability, non-aged/aged	EN 17990	Passed
Can be plastered over		Yes
Application temperature		Above -10 °C ; 14 °F
Temperature resistance		Permanent -40 °C to 90 °C ; -40 °F to 194 °F
Storage		Cool and dry

Areas of application

For exterior windtight joints that are resistant to driving rain between windows or doors and adjacent building structures, with three adhesive strips.

Supply form

Art. no.	Length	Width	Weight	Sales unit	Container	GTIN
11946	30 m	85 mm	0.85 kg	8	240	4026639119469
11947	30 m	120 mm	1 kg	8	240	4026639119476

Advantages

- ✓ Easy to work with: extra thin for easy folding in corner areas
- ✓ Independently confirmed suitability: tests in accordance with MO-01/1 passed at IFT in Rosenheim, Germany
- ✓ Reliable joints in combination with CONTEGA SL for interior use
- ✓ Fleece side can be plastered over: defined transition between window or wind sealing and plasterwork
- ✓ Flexible application: three adhesive strips for use with timber, masonry or concrete structures

Substrates

Clean substrates before sticking. Uneven mineral substrates may need to be levelled with a smooth plaster finish. Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on surfaces where adhesives are to be applied.

Observe the recommendations for plastering over adhesive tapes that are specified by the producer of the plaster. In most cases, it is recommended that the width of adhesive tape that is to be plastered over should not exceed 60 mm (2 3/8") or 50% of the reveal area. Subsurfaces must be sufficiently dry and stable; if necessary, substrates should be stabilised or renewed.


Permanent adhesion is achieved on all pro clima exterior membranes and on other underlay and breather (WRB) membranes (e.g. those made of PP and PET). Tapes can be applied to planed or painted wood, hard plastics, hard wood-based panels (chipboard, OSB and plywood panels). For sealing joints on masonry or concrete or on rough substrates, use ORCON F.

The best results in terms of reliability are achieved on high-quality substrates. Particular care is necessary when working with older or multi-layer substrates. It is your responsibility to check the suitability of the subsurface; adhesion tests may be necessary in certain cases. Pre-treatment of the subsurface with TESCON PRIMER will improve the adhesive bond.

General conditions

Taped joints should not be subjected to tensile strain. Rub the adhesive tapes firmly to secure the adhesive bonds. Ensure that there is sufficient resistance pressure. Seals that are windproof and resistant to driving rain can only be achieved if tapes have been installed without folds or creases.

When plastering, please observe the recommendations of the plaster manufacturer for non-absorbent substrates. A bonding course may be necessary.



Prüfbericht Nr. 14-001438-PR02
(PB-E03-020310-0e-02)
• CONTEGA SL EL ORCON F
• CONTEGA EXO EL ORCON F
nach MO-01/1:2007-01, Abs. 5
26.02.2016

**Made in
Germany**

developed and
produced by



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about installation and design details is available in the pro clima planning documentation. If you have any questions, please contact [pro clima Technical Support](<https://proclima.com/service/technical-support>).

MOLL

bauökologische Produkte GmbH
Rheinthalstraße 35 - 43
D-68723 Schwetzingen
Fon: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.de